

ProAc RESPONSE ONE 'S'



An exciting development in miniature loudspeaker design.

The RESPONSE range of loudspeakers from ProAc has redefined the state-of-the-art in loudspeaker performance.

The culmination of over twenty year's design experience, they incorporate the very finest components and materials available. Exhaustively researched and tested using the latest technology, the

RESPONSE range allows the full realisation of the potential of high quality ancillary equipment.

Although only slightly larger than the highly acclaimed ProAc Tablette 111, the Response One 'S' takes miniature loudspeaker performance into a new dimension.

The latest development of this hugely successful model incorporates a sensational new bass driver, manufactured exclusively for ProAc. The highly damped, completely transparent cone of this unit marries

 **ProAc**
perfectly natural



extreme rigidity to exceptional lightness, resulting in immense bass power and a wonderfully refined and open midrange.

Housed in a larger cabinet than previously, this dynamic new bass/midrange driver, working in tandem with an equalised reflex port, produces exceptional bass extension with greatly enhanced midrange transparency and detail. A modified high quality crossover network integrates the bass/midrange output with the effortless smoothness of the dome tweeter to provide seamless reproduction throughout the entire frequency range.

But perhaps the most important refinement is in the area of sound-staging. The drive units have been precisely offset in the two cabinet faces and the new mirror image configuration creates an incredibly large and spacious soundstage with exceptionally solid imagery. No expense has been spared in the design and construction of the Response One 'S'. The result is an outstandingly fast, powerful and accurate delivery combined with soundstaging not previously experienced from cabinets of this size.

SPECIFICATION

| | |
|--------------------------------|---|
| Nominal Impedance: | 8 ohms recommended |
| Recommended Amplifiers: | 20 to 100 watts |
| Frequency Response: | 40hz to 25Khz |
| Sensitivity: | 86db linear for 1 watt at 1 metre |
| Bass/Midrange Driver: | New 5" (127mm) unit with special transparent cone and phase plug mounted on die-cast chassis. High temperature voice coil and vented magnet assembly. |
| Tweeter: | ProAc ¾" (19mm) dome unit, with honeycomb-wound voice coil. Special damping and ferrofluid-cooled coil assembly. |
| Crossover: | Highest quality components as used on other Response models. Adaptable for bi-amping. |
| Dimensions: | 12" (305mm) high (on plinth). 7" (178mm) wide 9¼" (248mm) deep |
| Mode: | Stand mounted. |
| Grille: | Acoustically transparent crimplene. |
| Finish: | Teak, Walnut and Black Ash as standard. Others to order. |

* Due to our policy of continuous improvement all specifications are subject to change without notice.