

ProAc RESPONSE TWO 'S'



New levels of performance from a world-beating design.

Acclaimed worldwide by audiophiles and reviewers alike, the ProAc Response Two came to represent a benchmark in compact loudspeaker design.

Now its successor, the Response Two 'S', raises the game yet again. This new model is more than just a facelift of the original; a combination of new bass driver, cabinet redesign and a redeveloped crossover network has resulted in greatly improved levels of sonic performance.

The new cabinet is a major factor. Although of the same external dimensions as the original design, it has been constructed with walls of varying thickness and much heavier damping, so reducing colouration to inaudibility.

A special version of the bass driver used in the top Response range monitors has been developed for the Two 'S'. Lighter and more

 **ProAc**
perfectly natural



responsive, this new driver is loaded by a large equalised reflex rear port which increases bass extension and detail.

A special new magnet assembly provides more power and greatly enhances transient response.

Through a radically re-worked crossover, the bass unit harmonises perfectly with our incomparable soft dome tweeter, the pedigree of which was firmly established in the original Response Two.

The characteristic smoothness of this design has now been refined to the ultimate. The new Response Two 'S' delivers music with a seductive richness and warmth, yet without sacrificing detail or neutrality. And as with all ProAc models, an expansive soundstage and pinpoint imagery come as standard.

The full potential of these thoroughbred designs will only be realised through the use of the highest quality partnering equipment.

SPECIFICATION

Nominal Impedance:	8 ohms
Recommended Amplifiers:	20 to 175 watts
Frequency Response:	32hz to 30Khz
Sensitivity:	87db linear for 1 watt at 1 metre
Bass/Midrange Driver:	ProAc 6½" (165mm) polypropylene unit in die-cast chassis, with special magnet system, voice coil and pole piece.
Tweeter:	ProAc ¾" (19mm) soft dome with honeycomb -wound voice coil. Special damping and ferrofluid-cooled assembly.
Crossover:	Finest components on dedicated circuit board. Multistrand oxygen-free copper cable throughout. Split for optional bi-wiring and bi-amping.
Dimensions:	18" (457mm) high (on plinth). 9" (229mm) wide 11" (279mm) deep
Mode:	Stand mounted.
Grille:	Acoustically transparent crimplene.
Finish:	Available in the following real wood veneers: Black Ash, Walnut, Natural Oak, Mahogany, Cherry, Rosewood, Yew, Ebony, Bird's Eye Maple, Burr Oak.

* Due to our policy of continuous improvement all specifications are subject to change without notice.