

# ProAc RESPONSE THREE SIGNATURE



## **An impressive development of a great loudspeaker design.**

Ecstatically reviewed in the hi-fi press worldwide, the ProAc Response Three is acknowledged as one of the finest moving coil loudspeakers on the market.

Now this outstanding design has been refined both sonically and visually to create a striking new model — the Response Three Signature.

Any significant improvement in sound quality over the original design was naturally difficult to achieve, but was ultimately realised through a comprehensive upgrading of the signal paths.

A new rhodium-plated crossover network was conceived, designed to bolt directly to the rhodium terminals. Specially selected components including A/C chokes, silvered capacitors and ceramic wire-wound resistors were introduced into the network, mated to super quality wire throughout.

 **ProAc**  
*perfectly natural*



The contribution of the rhodium elements is a major factor and even extends to the drive units, which are secured by special rhodium bolts and to the floor coupling, which is improved by the use of rhodium spikes. All components are individually selected and each hand-built Signature is fine-tuned during testing.

The effects of these modifications are impressive. The Signature demonstrates a quite incredible neutrality, a faster and more powerful bass and a breathtaking soundstage with almost holographic imagery.

When a loudspeaker sounds this good, it should have the looks to match. The Signatures are available in a range of exquisite finishes designed to complement their outstanding performance.

A unique collection of exotic and expensive veneers, including Burr Oak, Burr Poplar and Silk Oak has been carefully selected for both aesthetic and environmental considerations. These classic finishes, combined with the revelatory sound quality, make the Signatures a triumph of British audio craftsmanship.

## SPECIFICATION

<b>Nominal Impedance:</b>	8 ohms
<b>Recommended Amplifiers:</b>	20 to 250 watts
<b>Frequency Response:</b>	20hz to 25Khz
<b>Sensitivity:</b>	89db linear for 1 watt at 1 metre
<b>Bass/Midrange Driver:</b>	ProAc 6½" (165mm) polypropylene unit in die-cast chassis with special damping, designed in conjunction with Scanspeak of Denmark. Special voice coil, pole piece, dustcap and magnet assembly.
<b>Tweeter:</b>	1" (25mm) dome with special coating and unique rear loading. Ferrofluid-cooled coil assembly.
<b>Crossover:</b>	Special rhodium-plated network, selected silvered components and highest grade wire.
<b>Dimensions:</b>	47" (1194mm) high (on plinth). 11" (279mm) wide 12" (304mm) deep
<b>Mode:</b>	Floorstanding on dedicated plinths.
<b>Grille:</b>	Acoustically transparent crimplene.
<b>Finish:</b>	Burr Oak, Burr Poplar, Birds Eye Maple, Silk Oak, Ebony.

\* Due to our policy of continuous improvement all specifications are subject to change without notice.