

ProAc RESPONSE FOUR



The exhilaration of full-scale musical performance.

Like no other loudspeakers on the market today, the Response Fours elevate domestic musical appreciation to an unforgettably lifelike experience. The full weight, scope and vitality of live music, be it symphony orchestra, jazz band or rock concert is accurately and convincingly portrayed in an expansive soundstage with every slight detail of the original performance revealed. The listener becomes completely enveloped in compelling music on a grand scale.

An inspired progression of the current Response range which has been so enthusiastically received by audiophiles worldwide, the Response Fours represent the culmination of our long audio experience. Exquisitely crafted, no expense has been spared in their development, design or manufacture.

 **ProAc**
perfectly natural



Housed in each of the formidable cabinets is an impressive array of the finest drive units available. Primarily produced for high quality monitoring applications, the two nine-inch bass drivers, two large soft-dome midrange units and specialist soft dome tweeter are harmonised through a complex and expensive handbuilt crossover network. The result is soundstaging, pinpoint imagery and seamless neutrality previously unimagined from moving coil loudspeakers.

The Response Fours are available in standard ProAc veneers and a special range of exotic finishes to order. In both performance and appearance, these are loudspeakers for true connoisseurs of recorded music.

SPECIFICATION

Nominal Impedance:	8 ohms
Recommended Amplifiers:	50 to 500 watts
Frequency Response:	20hz to 25Khz
Sensitivity:	89db linear for 1 watt at 1 metre
Bass Drivers:	(2 per cabinet) Studio quality 9" (229mm) coated cones with 3" (76mm) ribbon wound voice coil and die-cast chassis, mounted on pro-fessional magnet assembly.
Midrange Drivers:	(2 per cabinet) Studio quality 3" (76mm) soft dome with 3" (76mm) ribbon wound voice coil and double suspension, mounted on professional magnet assembly.
Tweeter:	ProAc 1" (25mm) soft dome with exclusive coating. Unique rear loading, ferrofluid cooled and damped voice coil.
Crossover:	Super high grade fibreglass base with higher purity heavy grade tracking, AC chokes, silvered capacitors and high wattage ceramic resistors.
Dimensions:	63" (1600mm) high (on plinths with spikes). 14" (356mm) wide 17" (432mm) deep
Mode:	Floorstanding on dedicated plinths and spikes.
Grille:	Acoustically transparent crimplene.
Finish:	Walnut, Black Ash as standard. Teak, Oak, Mahogany to order at no extra cost. Ebony, Burr Oak, Birds Eye Maple to order-extra premium.

* Due to our policy of continuous improvement all specifications are subject to change without notice. Cabinets pictured are finished in burr oak real wood veneer. Since wood is a natural product, both colour and grain patterns may vary.