

ProAc **RESPONSE D15**



With its roots in the highly acclaimed Response One Point Five, this elegant new model delivers a heightened level of dynamic performance, adding greater weight and a lively muscularity to the musical experience.

At the hub of this improvement is our own new 6½" bass/midrange unit. This driver has a radical new basket design for higher rigidity and a completely reworked magnet and coil assembly. Bass loading is achieved through a system which has never been used before in a Response range model. Four large conical feet support each cabinet, allowing the flared equalised ports to couple the bass output efficiently to the floor through the plinths. As a result this driver excels in areas of control, power handling, openness and midrange detail.

ProAc **RESPONSE D15**

*Audiophile excellence
in a dynamic new
floorstanding design*

 **ProAc**
perfectly natural



ProAc **RESPONSE D15**

Through a sophisticated crossover network the bass/midrange driver is harnessed to the famous ProAc $\frac{3}{4}$ " soft dome tweeter, which has become renowned for its smooth, sweet and detailed sound.

As ever Response range build quality is outstanding. A high density MDF cabinet with walls of varying thickness is heavily damped with bitumen and lined with anechoic grade foam. Finished in real wood veneers, these superb cabinets are built to look good for a long time.

The new D15 is a remarkable fulfilment of the promise of cutting edge technology, producing a powerful yet refined presentation of music out of all proportion to the size of the cabinets. These are floorstanders with a beguiling musicality which will satisfy the most demanding of audiophiles.



Specification

| | |
|------------------------|--|
| Nominal Impedance | 8 ohms |
| Recommended Amplifiers | 20 to 180 watts |
| Frequency Response | 30hz to 30Khz |
| Sensitivity | 88db linear for 1 watt at 1 metre |
| Bass/Midrange Driver | 6 $\frac{1}{2}$ " diameter unit with new rigid chassis. Linear motor assembly and large copper magnet and phase plug. Glass fibre weave cone exclusive to ProAc. |
| Tweeter | $\frac{3}{4}$ " soft dome exclusive to ProAc with special honeycomb wound voice coil and rear chamber damping |
| Crossover | Finest components on dedicated circuit board. Multistrand oxygen-free copper cable throughout. Split for optional bi-wiring and bi-amping. |
| Dimensions | 38 $\frac{3}{4}$ " (984mm) high on plinths with conical feet 7 $\frac{1}{2}$ " (190mm) wide 10" (254mm) deep |
| Weight | 50 lbs (23kg) /cabinet |
| Mode | Floorstanding |
| Grille | Acoustically transparent crimplene |
| Finish | Available in the following real wood veneers: Black Ash, Maple, Cherry, Mahogany, Yew, Ebony, Bird's Eye Maple |

* Due to our policy of continuous improvement specifications are subject to change without notice. Cabinets pictured are finished in Cherry real wood veneer. Since wood is a natural product both colour and grain patterns may vary.